ILLUMINOMETER

PCE-170 A



- **Large 5-digit LCD display**
- **Measurement range from 0.00 to 40,000 lux**
- **Resolution of 0.01 lux in a range up to 39.99 lux**
- **Sensor: silicon photodiode**
- **Corrected cosine angle**
- **HOLD function**
- **Fast and accurate response**
- **Auto shut-off after 30 min.**
- **1 x 9V battery and carrying case**
- **Selectable units: lx and fc (fc = footcandle; 1 fc=10,764 lx)**
- **Selectable manual or automatic range**

The PCE-170 A Illuminometer is well-known for its durability as well as its good quality at a good price. The PCE-170 A Illuminometer has a wide measurement range. Thanks to its fast response time and compact housing you can use this meter with just one hand. The PCE-170 A Illuminometer can be used even by inexperienced personnel. With the PCE-170 A Illuminometer you will be able to perform a professional valuation. The PCE-170 A Illuminometer can be widely used within the industrial sector. For example, it is possible to check light conditions in workplaces, warehouses, industries and apartments with the PCE-170 A Illuminometer.In addition, emergency escape routes can be tested with the PCE-170A Illuminometer for proper illumination. The PCE-170 A Illuminometer is an irreplaceable instrument to prevent occupational hazards and it meets professional standards.

Workplaces will become safer and you will save expenses. Latest research has discovered that too little as well as too much illumination in a workplace can be harmful for humans. You can also check illumination at home, in your dining-room for instance. The digital PCE-170 A Illuminometer measures in Lux units (lumen/m^2 or lumen/$foot^2$). This solid and portable PCE-170 A Illuminometer provides very accurate results and comes with a zero-reset function when it is on. It also has a sensor with a response curve for all the visible spectrum.

Specification

Light	
Measuring range	0 lx ... 40 klx
Resolution	0,01 lx
Accuracy	±10 % of Rd +5 digits (corresponds to class B / DIN 5032 part 7)
Light	
Measuring range	0 fc ... 4 kfc
Resolution	0,001 fc
Accuracy	±10 % of Rd +5 digits (corresponds to class B / DIN 5032 part 7)

General technical data	
Units	lx, FC
Display type	LCD
Measuring rate	2 Hz
Classification	Class B
Standard(s)	DIN 5032-7
Operating time	170 h
Measurement range selection	Manual, Automatic
Measurement range selection additional information	0.00 bis 39.99 / 399.9 / 3999 / 39990 lx 0.000 bis 3.999 / 39.99 / 399.9 / 3999 fc
Operating height	2000 m max. above sea level
Menu language	English
Protection class (device)	IP20
(Rechargeable) battery	1 x 9 V 9V block , Alkali-manganese
Capacity	640 mAh
Operating conditions	0 ... 40 °C , 0 ... 90 % RH
Storage conditions	-10 ... 50 °C , 0 ... 70 % RH
Dimensions (L x W x H)	196 x 54 x 34 mm
Weight	150 g